

# PB | HYDRAULIC PIPE BENDER




- ▶ Lightweight aluminium bending frame
- ▶ Designed to offer smooth, wrinkle free bend on various sizes and thicknesses of JIS standardised conduit pipes
- ▶ For use on pipe sizes from 16 to 82 mm (½" to 3")
- Can be operated by manual or powered pumps up to 700 bar
- ▶ Portable and easy to use
- ▶ Bending shoes are available as individual items

# **Capacity 10 tonnes**

### Bends up to 90 degrees

# Working pressure 700 bar



Model	Max capacity (tonnes)	Stroke (mm)	Oil capacity (litres)	Weight (kg)	Applicable range / included bending shoes	Dimensions (mm)							
number						Α	В	С	D	E	F	G	Н
PB10B	10	250	0.4	62.5	Thick steel conduit from 16 mm (½") to 82 mm (3")	720	147	755	695	595	495	395	295

Note: Weight for PB10B includes metal storage box but excludes pump and hose.

#### **BENDING SHOES**

Model number	For thick steel conduit from 16 mm ( $1/2$ ") to 82 mm (3")								
Model number	Pipe size (inch)	Pipe outer diameter (mm)	Pipe inner diameter (mm)	Bending radius (mm)					
BS-B16	1/2"	21	16.4	75					
BS-B22	3/4"	26.5	21.9	90					
BS-B28	1"	33.3	28.3	130					
BS-B36	1 1/4"	41.9	36.9	195					
BS-B42	1 ½"	47.8	42.8	230					
BS-B54	2"	59.6	54	270					
BS-B70	2 ½"	75.2	69.6	450					
BS-B82	3"	87.9	82.3	500					